


Dutch Canopy CN20



**DUTCH CANOPY
COMPONENT BOOK**

CN20

INDEX

Page

Beskrivning Description Beschreibung	2-4
Sprängskiss Exploded view Explosionsdarstellung	5
Komponenter Components Komponenten	6-14
Handverktyg Handtools Handwerkzeuge	15
Korsreferens Cross reference Zubehör	16
Kapmått Fabrication guidelines Abschneidemaße	17
Materialkalkyl Bill of material Komponenten Aufstellung	18-19
Modeller Models Modelle	20

FÖRKLARINGAR

* Efter ett artikelnummer hänvisar till rekommenderad skruv etc.

EXPLANATIONS

* After an article number refers to recommended screw etc.

ERKLÄRUNGEN

* Nach einer Bestellnummer weist auf empfohlene Schraube hin, usw.

Beskrivning

Användningsområde

CN20 är en extra kraftig korgmarkis för de flesta byggnader, t ex villor, kontor och butiker.

CN20 kan tillverkas i många olika varierande modeller och lämpar sig mycket väl för tillverkning av baldakiner.

Manövrering

Utvändig manövrering med lina, växel eller motor.

Invändig manövrering med motor. Motorn kan kompletteras med automatiska styrningar, t ex fjärrkontroll eller sol- och vindautomatik.

Montering

Markisen monteras ovanför fönster eller över entréer.

Komponenter

Gångjärn, beslag och hörnbågar är tillverkade av pressgjutet eller strängpressat aluminium. Den löstagbara veven i stål är pulverlackerad. Pulverlackerade artiklar har färgnummer 0058 för silver (RAL 9006). Obehandlade eller galvaniserade artiklar har färgnummer 0000.

Fästelement är tillverkade av rostfritt stål, förzinkat stål eller ytbehandlat med Dacro. 500 LC.

Profiler

Profiler till bågar är tillverkade av strängpressat aluminium. Naturanodiserade aluminiumprofiler har färgnummer 0000 och obehandlade 0100.

Dimensioner

Utfall: 0.4 – 2.0 m.

Max. bredd 6.0 m per enhet.

Ovanstående mått är rekommenderade maxmått som inte bör överskridas. Vid svåra monteringsförhållanden bör även dessa maxmått övervägas.

Icke standard artiklar

Artikelnummer markerade med "Nonstandard" lagerförs inte och har därför längre leveranstid. Minsta orderkvantitet (Min) gäller.

Vi förbehåller oss rätten till konstruktionsändringar.

Description

Range of application

CN20 is a heavy-duty Dutch canopy for most buildings, e.g. restaurants, kiosks, shops, hotels, offices and villas. CN20 can be produced in many different models and is suitable also for walkways.

Operation

Exterior operation with cord, gear or motor. Interior operation with motor. The motor can be completed with automatic controls, for example remote control or sun and wind sensors.

Installation

The awning can be installed above windows or over entrances.

Components

Hinges, fittings and hoop corners are manufactured of die-cast or extruded aluminium. The removable crank handle is powder coated. Powder coated articles have colour code 0058 for silver (RAL 9006). Untreated or galvanised articles have colour code 0000.

Fasteners are manufactured of stainless steel, zinc plated steel or surface treated with Dacro. 500 LC.

Profiles

Canopy hoops are manufactured of extruded aluminium. Clear anodised profiles have colour code 0000 and untreated 0100.

Dimensions

Projection 0.4 – 2.0 m (1'4" – 6'7").

Max width 6.0 m (19'8") per unit.

The maximum measurements are recommended and should not be exceeded. If the installation conditions are difficult, even these dimensions should be reconsidered.

Nonstandard articles

Articles marked with "Nonstandard" are not kept in stock, which results in longer delivery times. Minimum order quantities (Min) apply.

Subject to changes without notice.

Beschreibung

Einsatzgebiete

CN20 ist eine sehr robuste Korbmarkise für die meisten Gebäude, z.B. an Villen, Schulen, Büros, Krankenhäusern usw. geeignet sind. CN20 kann jedem Stil des Hauses angepasst werden und lässt keine Wünsche offen, bis hin zum Baldachin.

Bedienung

Die Bedienung von außen erfolgt wahlweise mittels Handkurbel, Schnur oder Motor, von innen mittels Motor. Für den Motor sind automatische Steuerungen, z.B. Fernbedienung oder Sonnen- und Windautomatik erhältlich.

Montage

Die Markise kann über Fenster oder Overeingänge angebracht werden.

Komponenten

Scharniere, Befestigungen und Bandecken sind aus Aluminium stranggepresst oder Hochdruckguss. Die abnehmbare Handkurbel ist aus Stahl ist pulverbeschichtet. Die pulverbeschichteten Teile haben die Farbenbezeichnung 0058 für Silber (RAL 9006). Unbehandelte oder galvanisierte Teile haben die Farbenbezeichnung 0000.

Die Befestigungsteile sind aus rostfreiem Stahl, verzinktem Stahl oder mit Dacrolit 500 LC gefertigt.

Profile

Spiegelprofil, Kupplungsprofil und Schnurführungsprofil sind aus stranggepresstem Aluminium. Natureloxierte Aluminiumprofile haben Farbenbezeichnung 0000 und unbeschichtete 0100.

Maße

Ausfall: 0.4 – 2.0 Mtr.

Max. Breite: 6.0 Mtr.

Diese Maximalmaße sind empfohlen und sollten nicht überschritten werden. Bei schwierigen Montagebedingungen sollten auch diese Max.-Maße überdacht werden.


Nonstandard Artikel





Bestell-Nr., die mit der Kennung „Nonstandard“ ausgeschrieben sind, werden nicht auf Lager. Daher verlängert sich bei diesen Artikeln die Lieferzeit. Auch Mindestbestellmengen sind erforderlich.





Technische Änderungen vorbehalten











Exploded view CN20











	Article No.	Description	Note	Stand. pack
		Installation bracket Aluminium Monteringskonsol Aluminium Wandträger Aluminium		
	78.0221.0058	* 66.1030, 66.1155 Silver Silber		20
		Base profile Aluminium Basprofil Aluminium Spiegelprofil Aluminium	45 x 16 mm	
	74.5201.0000	(19'8")	16 x 6 m	96 m
		Joining piece Aluminium, for base profile 74.5201 Skarvprofil Aluminium, för basprofil 74.5201 Kupplung Aluminium, für Spiegelprofil 74.5201	21 x 13 mm	
	74.5204.0100	(13'1")		4.0 m
		Strengthening profile Aluminium, for fixed canopy hoops Förstärkningsprofil Aluminium, för fasta bågar Verstärkungsprofil Aluminium, für feste Bogen	25 x 5 mm	
	77.4608.0000	(19'8")		6 m





	Article No.	Description	Note	Stand. pack
		Base hinge Aluminium Basgångjärn Aluminium Scharnier, Anfang Aluminium		
	78.0160.0058	Silver Silber		20
		Centre hinge Aluminium Mellångångjärn Aluminium Scharnier, Mittelstück Aluminium	Part "A"	
	78.0163.0058	Silver Silber		20
		Centre hinge Aluminium Mellångångjärn Aluminium Scharnier, Mittelstück Aluminium	Part "B"	
	78.0164.0058	Silver Silber		20
		Front hinge Aluminium Slutgångjärn Aluminium Scharnier, Endstück Aluminium	Part "C"	
	78.0165.0058	Silver Silber		20




	Article No.	Description	Note	Stand. pack
		Front hinge Aluminium Slutgångjärn Aluminium Scharnier, Endstück Aluminium	Part "D"	
	78.0166.0058	Silver Silber		20
		Base hinge Profile mounting Aluminium, for front hinge 78.0165-66 Basgångjärn Klättrande bågar Aluminium, för slutgångjärn 78.0165-66 Scharnier Profilmontage Aluminium, für Scharnier, Endstück 78.0165-66 * 66.1030, 66.1155		
	78.0062.0058	Silver Silber		20
		Profile connector Walkways Aluminium, for base profile 74.5201 Profilförbindelse Baldakin Aluminium, för basprofil 74.5201 Profilverbindung Baldakin Aluminium, für Spiegelprofil 74.5201 * 66.1030, 66.1155		
	78.0141.0058	Silver Silber		20
		Adjustable corner Aluminium, radius 35 mm Ställbart hörn Aluminium, radie 35 mm Eckverbinder, einstellbar Aluminium, Radius 35 mm	90°-180°	
	78.0181.0058	Silver Silber		10




	Article No.	Description	Note	Stand. pack
		Fixed corner Aluminium, radius 75 mm Fast hörn Aluminium, radie 75 mm Eckverbinder Aluminium, Radius 75 mm		
	78.0041.0058	Silver Silber		10
		Bent base profile Aluminium 45 x 16 mm Böckad basprofil Aluminium Spiegelprofil gebogen Aluminium		
	78.4001.0000	L 900 mm (3')		1
	78.4002.0000	L 620 mm (2')		1
		Cord guide profile Aluminium 25 x 16 mm Linstyrningsprofil Aluminium Schnurführungsprofil Aluminium		
	74.5601.0000	(9'10")		3 m
		Centre support and cord guide bracket Aluminium, for base profile 74.5201 and cord guide profile 74.5601 Mittstöds- och linstyrningskonsol Aluminium, basprofil 74.5201 och linstyrningsprofil 74.5601 Mittelstütze und Schnurführungskonsole Aluminium, für Spiegelprofil 74.5201 und Schnurführungsprofil 74.5601 * 66.1030, 66.1155		
	78.0122.0058	Silver Silber		20




	Article No.	Description	Note	Stand. pack
	78.2022.0000	End piece Cord guide Aluminium, for cord guide profile 74.5601 Ändbeslag Linstyrning Aluminium, för linstyrningsprofil 74.5601 Endstück Schnurführung Aluminium, für Schnurführungsprofil 74.5601		10
	77.7216.0000	Fixing plate for cord wheel Steel, zinc plated Fästplatta för linhjul Stål, förzinkad Halbeplatte für Blockrolle Stahl, verzinkt		10
	78.0092.0000	Cord wheel POM and steel, zinc plated Linhjul POM och stål, förzinkad Blockrolle POM und Stahl, verzinkt		50
	68.1040.5000	Cord Polyester, with centre core Lina Polyester, med kärna Aufzugschnur Polyester, mit Einlage	Vit White Weiss	130 m
			K 40	

	Article No.	Description	Note	Stand. pack
		Cord guide Steel, zinc plated Brytbeslag Stål, förzinkat Schnurbeslag Stahl, verzinkt * 66.1086		
	77.7210.0001	Vit White Weiss		10
		Cord inlet Steel, nickel plated Lingenomföring Stål, förnicklad Durchführung für Schnur Stahl, glanzverzinkt		
	77.7212.0000			10
		Cleat Zinc Knap Zink Seilschloss Zink		
	77.3304.0000			25
		Cleat Polyamide Knap Polyamid Seilschloss Polyamid * 66.1086		
	77.6730.0058	Silver Silber		25

	Article No.	Description	Note	Stand. pack
		Tassel ABS, for tape and cord		
		Bandknopp ABS, för band och lina		
		Quaste ABS, für Band und Schnur		
	71.2301.0001	Vit White Weiss		100
	71.2301.0182	Silver Silber		100
		Crank box with crank handle Complete, 2:1, installed internally	86 x 121 x 44 mm	
		Vevbox med vev Komplett, 2:1, monteras invändigt		
		Kurbelkasten mit Handkurbel Komplett, 2:1, für innen montage		
		* 66.1088		
	77.9310.0001	Vit White Weiss	Max 40 kg	1
		Crank handle Spare part for crank box with crank handle 77.9310		
		Vev Reservdel för vevbox med vev 77.9310		
		Handkurbel Erzatzteil für Kurbelkasten mit Handkurbel 77.9310		
	77.9322.0001	Vit White Weiss		1
		Filling profile PVC		
		Fästlist PVC		
		Nagel-Keder PVC		
	78.0204.0001	Vit White Weiss		100 m

	Article No.	Description	Note	Stand. pack
		Decoration profile PVC Dekorlist PVC Zierprofil PVC		
	77.6500.0005	Mörkgrön Dark green, Non-stock item, min qty 200 m		200 m
	77.6500.0011	Röd Red, Non-stock item, min qty 200 m		200 m
	77.6500.0012	Gul Yellow, Non-stock item, min qty 200 m		200 m
	77.6500.0013	Blå Blue, Non-stock item, min qty 200 m		200 m
	77.6500.0014	Mörkbeige Dark beige, Non-stock item, min qty 200 m		200 m
	77.6500.0015	Vit White, Non-stock item, min qty 200 m		200 m
	77.6500.0024	Svart Black, Non-stock item, min qty 200 m		200 m
	77.6500.0052	Beige, Non-stock item, min qty 200 m		200 m
	77.6500.0054	Ockra Ochre, Non-stock item, min qty 200 m		200 m
	77.6500.0073	Vinröd Vinered, Non-stock item, min qty 200 m		200 m
	77.6500.0075	Marinblå Navy blue, Non-stock item, min qty 200 m		200 m
	77.6500.0079	Grå Grey, Non-stock item, min qty 200 m		200 m
	77.6500.0081	Brun Brown, Non-stock item, min qty 200 m		200 m
	77.6500.0084	Rost Rust, Non-stock item, min qty 200 m		200 m
	77.6500.0151	Krämvit Off-white, Non-stock item, min qty 200 m		200 m
		Plastic hose Polyethylene, for packaging of components Plastslang Polyeten, för emballering av komponenter Kunststoffschlauch Polyäthylenen, zum verpacken der Komponenten		
	77.9900.0000	(1640ft) W 0.23 m (9"), Thickness 0.10 mm		500 m
	77.9901.0000	(1640') W 0.5m (1'7"), Thickness 0.10 mm		500 m
		T-slot bolt Stainless steel T-spårskruv Rostfritt stål T-Schlitzschraube Edelstahl-Rostfrei	Spanner 12 mm	
	66.1030.0000		M6x12	100

	Article No.	Description	Note	Stand. pack
	66.1203.0000	Screw for installation Steel, Protect 4	Spanner 8 mm	100
		Monteringsskruv Stål, Protect 4		
		Befestigungsschraube Stahl, Protect 4		
			6x40	
	66.1100.0000	Washer Stainless steel		100
		Bricka Rostfritt stål		
		Unterlegscheibe Edelstahl rostfrei		
		Rondelle Acier inoxydbale		
			6.7x14x1.5	
	66.1155.0000	Flange nut Stainless steel	Spanner 10 mm	100
		Flänsmutter Rostfritt stål		
		Flanschenmutter Edelstahl rostfrei		
			M6	

	Article No.	Description	Note	Stand. pack
		Power unit Without tool		
	89.8001.0000	Aruba, Siesta, Sienna, Arista, Ronda, Venezia		
		Stamping tool For profile 74.5201, Requires power unit 89.8001		
	89.8002.0000	CN20		
		Assembly tool For mounting of filling profile 78.0204		
	90.8007.0000	CN20		

Cross reference

Description	Article No.	Articles for assembly	Quantity
Base hinge	78.0062	66.1030	1
		66.1155	1
Centre support	78.0122	66.1030	2
		66.1155	2
Profile connector	78.0141	66.1030	1
		66.1155	1
Installation bracket	78.0221	66.1030	1
		66.1155	1
Installation of brackets		66.1203	1

Fabrication guidelines CN20

Number of hoops per projection

Projection	Hoops	Hoops
	Type A	Type B
	[PCS]	[PCS]
≤ 900 mm (3')	4	4
≤ 1000 mm (3'4")	5	4
≤ 1300 mm (4'3")	5	5
≤ 1500 mm (4'11")	6	5
≤ 1600 mm (5'3")	6	6
≤ 2000 mm (6'7")	7	6

Number of installation brackets and centre arms per awning width for type A and B

Width	Installation brackets	Centre arms
	[PCS]	[PCS]
≤ 1600 mm (5'3")	2	0
≤ 2800 mm (9'2")	3	0
≤ 3500 mm (11'6")	4	0
≤ 4500 mm (14'9")	5	1
≤ 6000 mm (19'8")	6	1

For projections over 1200 mm (3'11") installation brackets should be used also on the vertical profiles of the wall hoop

Bill of material: CN20 type A with cord operation

Projection: 800 mm
Width: 2000 mm
Number of hoops: 3


Description	Colour	Qty			Unit	Stand. Pack
	[Silver]	Model A35	Model A75	Model A170		[Unit]
Base profile	74.5201.0000	10.8	10.8	6.0	m	96
Filling profile	78.0204.0001	12.0	12.0	12.0	m	100
Base hinge	78.0160.0058	2	2	2	PCS	20
Centre hinge	78.0163.0058	2	2	2	PCS	20
Centre hinge	78.0164.0058	2	2	2	PCS	20
Front hinge	78.0165.0058	2	2	2	PCS	20
Front hinge	78.0166.0058	2	2	2	PCS	20
Installation bracket	78.0221.0058	3	3	3	PCS	20
T-slotted bolt	66.1030.0000	3	3	3	PCS	100
Flange nut	66.1155.0000	3	3	3	PCS	100
Adjustable corner	78.0181.0058	6	-	-	PCS	10
Fixed corner	78.0041.0058	-	6	-	PCS	10
Arm profile	78.4001.0000	-	-	6	PCS	1
Joining piece	74.5204.0100	-	-	3.0	m	4
Centre support bracket	78.0122.0058	3	3	3	PCS	20
T-slotted bolt	66.1030.0000	6	6	6	PCS	100
Flange nut	66.1155.0000	6	6	6	PCS	100
Cord guide profile	74.5601.0000	0.6	0.6	0.6	m	6
End piece	78.2022.0000	3	3	3	PCS	10
Cord wheel	78.0092.0000	2	2	2	PCS	20
Cord cleat	77.3304.0000	1	1	1	PCS	25
Decoration profile	77.6500.xxxx	12.0	12.0	12.0	m	200
Cord	68.1040.5000	6.0	6.0	6.0	m	130
For additional hoops add						
Base profile	74.5201.0000	3.6	3.6	2.0	m	96
Filling profile	78.0204.0001	4.0	4.0	4.0	m	100
Centre hinge	78.0163.0058	2	2	2	PCS	20
Centre hinge	78.0164.0058	2	2	2	PCS	20
Decoration profile	77.6500.xxxx	4.0	4.0	4.0	m	200
Adjustable corner	78.0181.0058	2	-	-	PCS	10
Fixed corner	78.0041.0058	-	2	-	PCS	10
Arm profile	78.4001.0000	-	-	2	PCS	1
Joining piece	74.5204.0100	-	-	1.0	m	4
Centre support bracket	78.0122.0058	1	1	1	PCS	20
T-slotted bolt	66.1030.0000	2	2	2	PCS	100
Flange nut	66.1155.0000	2	2	2	PCS	100
Cord guide profile	74.5601.0000	0.2	0.2	0.2	m	6
End piece	78.2022.0000	1	1	1	PCS	10
Cord wheel	78.0092.0000	1	1	1	PCS	20
For interior cord operation add						
Cord guide	77.7210.0001	2	2	2	PCS	10
Cord inlet	77.7212.0000	2	2	2	PCS	10

Bill of material: CN20 type B with cord operation

Projection: 800 mm
Width: 2000 mm
Number of hoops: 3 + 1


Description	Colour	Qty			Unit	Stand. Pack [Unit]
	[Silver]	Model B35	Model B75	Model B170		
Base profile	74.5201.0000	14.2	14.2	8.0	m	96
Filling profile	78.0204.0001	16.0	16.0	16.0	m	100
Base hinge	78.0160.0058	2	2	2	PCS	20
Centre hinge	78.0163.0058	2	2	2	PCS	20
Centre hinge	78.0164.0058	2	2	2	PCS	20
Front hinge	78.0165.0058	4	2	2	PCS	20
Front hinge	78.0166.0058	4	2	2	PCS	20
Base hinge	78.0062.0058	2	2	2	PCS	20
T-slotted bolt	66.1030.0000	2	2	2	PCS	100
Flange nut	66.1155.0000	2	2	2	PCS	100
Installation bracket	78.0221.0058	3	3	3	PCS	20
T-slotted bolt	66.1030.0000	3	3	3	PCS	100
Flange nut	66.1155.0000	3	3	3	PCS	100
Adjustable corner	78.0181.0058	8	-	-	PCS	10
Fixed corner	78.0041.0058	-	8	-	PCS	10
Arm profile	78.4001.0000	-	-	8	PCS	1
Joining piece	74.5204.0100	-	-	4.0	m	4
Centre support bracket	78.0122.0058	4	4	4	PCS	20
T-slotted bolt	66.1030.0000	8	8	8	PCS	100
Flange nut	66.1155.0000	8	8	8	PCS	100
Cord guide profile	74.5601.0000	0.8	0.8	0.8	m	6
End piece	78.2022.0000	4	4	4	PCS	10
Cord wheel	78.0092.0000	3	3	3	PCS	20
Cord cleat	77.3304.0000	1	1	1	PCS	25
Decoration profile	77.6500.xxxx	16.0	16.0	16.0	m	200
Cord	68.1040.5000	8.0	8.0	8.0	m	130
For additional hoops add						
Base profile	74.5201.0000	3.9	3.9	2.0	m	96
Filling profile	78.0204.0001	4.0	4.0	4.0	m	100
Centre hinge	78.0163.0058	2	2	2	PCS	20
Centre hinge	78.0164.0058	2	2	2	PCS	20
Decoration profile	77.6500.xxxx	4.0	4.0	4.0	m	200
Adjustable corner	78.0181.0058	2	-	-	PCS	10
Fixed corner	78.0041.0058	-	2	-	PCS	10
Arm profile	78.4001.0000	-	-	2	PCS	1
Joining piece	74.5204.0100	-	-	1.0	m	4
Centre support bracket	78.0122.0058	1	1	1	PCS	20
T-slotted bolt	66.1030.0000	2	2	2	PCS	100
Flange nut	66.1155.0000	2	2	2	PCS	100
Cord guide profile	74.5601.0000	0.2	0.2	0.2	m	6
End piece	78.2022.0000	1	1	1	PCS	10
Cord wheel	78.0092.0000	1	1	1	PCS	20
For interior cord operation add						
Cord guide	77.7210.0001	2	2	2	PCS	10
Cord inlet	77.7212.0000	2	2	2	PCS	10

Type A




A35

- Classic - small radius
- 35 mm corner radius
- Projection equal to height
- Retractable or fixed




A75

- Classic - medium radius
- 75 mm corner radius
- Projection equal to height
- Retractable or fixed



A170


- Classic - large radius
- 170 mm corner radius
- Projection equal to height
- Retractable or fixed



A1


- Classic - combination
- Wall hoop has smaller radius than the other hoops
- Projection equal to height
- Retractable or fixed

Type B




B35

- Stepped canopy - small radius
- 35 mm corner radius
- Projection less than height
- Retractable or fixed




B75

- Stepped canopy - medium radius
- 75 mm corner radius
- Projection less than height
- Retractable or fixed



B170


- Stepped canopy - large radius
- 170 mm corner radius
- Projection less than height
- Retractable or fixed



B1


- Stepped canopy - combination
- Wall hoop has smaller radius than the other hoops
- Projection less than height
- Retractable or fixed

Type C




C1

- Round canopy
- Width equal to twice the projection
- Retractable or fixed



C2


- Curved canopy
- Width more than twice the projection
- Retractable or fixed



C3


- Cupola canopy
- Vertical hoops
- Fixed

Type D




D1

Type E



E1



E2

HUNTER DOUGLAS SCANDINAVIA

PO Box 541

SE-441 15 Alingsås

Sweden

Tel: +46-322 775 00

Fax: +46-322 775 99

E-mail: order@hunterdouglas.se



www.hunterdouglas.se

® Registered Trade Mark of Hunter Douglas Scandinavia AB, Sweden